


















**Stabil-Schraube mit Hülse**

Messing brüniert



Bezeichnung	Bestell-/Hersteller-Nr.	Ø ≠	⊞	CHF
Stabil-Schraube mit Hülse	60.1900.22 M3.5x35	738-4-8	100/20 St	3.80
Stabil-Schraube mit Hülse	60.1900.22 M3.5x40	743-5-3	100/20 St	4.05
Stabil-Schraube mit Hülse	60.1900.22 M3.5x45	748-5-8	100/20 St	3.95
Stabil-Schraube mit Hülse	60.1900.22 M3.5x50	753-6-3	100/20 St	4.35
Stabil-Schraube mit Hülse	60.1900.22 M3.5x55	758-6-8	100/20 St	4.15
Stabil-Schraube mit Hülse	60.1900.22 M3.5x60	763-7-3	100/20 St	4.25

**Piktogramme für Massangaben**

-  Breite über alles
-  Rosettenbreite
-  Höhe über alles
-  Rosettenhöhe
-  Grifflänge
-  Ausladung
-  Ausladung bis Mitte Bohrung
-  Einlasstiefe
-  Distanz Drückerloch – oberes Schraubenloch
-  Durchmesser (Bohrung, Dorn, Stange, Rohr, Seil oder Ansatz)
-  Stiftquerschnitt
-  Schraubenlochdistanz
-  Überschlag
-  Materialstärke
-  Gewinde, Schrauben, Bolzen
-  Mass A
-  Packungsgrösse/Staffelrabatt