

Innensechskant-Schraube DUROQUICK®

Stahl 45 H geschwärzt



Bezeichnung	Bestell-/Hersteller-Nr.			CHF
Innensechskant-Schraube Duroquick®	60.1902.13 M5x5	100/20	St	0.50
Innensechskant-Schraube Duroquick®	60.1902.13 M5x6	100/20	St	0.50
Innensechskant-Schraube Duroquick®	60.1902.13 M5x8	100/20	St	0.50
Innensechskant-Schraube Duroquick®	60.1902.13 M6x5	100/20	St	0.50
Innensechskant-Schraube Duroquick®	60.1902.13 M6x6	100/20	St	0.55
Innensechskant-Schraube Duroquick®	60.1902.13 M6x8	100/20	St	0.55

Piktogramme für Massangaben

-  Breite über alles
-  Rosettenbreite
-  Höhe über alles
-  Rosettenhöhe
-  Grifflänge
-  Ausladung
-  Ausladung bis Mitte Bohrung
-  Einlasstiefe
-  Distanz Drückerloch – oberes Schraubenloch
-  Durchmesser (Bohrung, Dorn, Stange, Rohr, Seil oder Ansatz)
-  Stiftquerschnitt
-  Schraubenlochdistanz
-  Überschlag
-  Materialstärke
-  Gewinde, Schrauben, Bolzen
-  Mass A
-  Packungsgrösse/Staffelrabatt