


















**Linsensenschraube**

Stahl verzinkt - passend zu poliert verchromt und matt verchromt



Bezeichnung	Bestell-/Hersteller-Nr.		CHF
Linsensenschraube	60.1983 3.0x20	200/20 St	0.35
Linsensenschraube	60.1983 3.5x20	200/20 St	0.35
Linsensenschraube	60.1983 3.5x25	200/20 St	0.35
Linsensenschraube	60.1983 4.0x20	200/20 St	0.35
Linsensenschraube	60.1983 4.0x25	200/20 St	0.35
Linsensenschraube	60.1983 4.0x30	200/20 St	0.35
Linsensenschraube	60.1983 4.0x35	200/20 St	0.35
Linsensenschraube	60.1983 4.0x40	200/20 St	0.35

**Piktogramme für Massangaben**

-  Breite über alles
-  Rosettenbreite
-  Höhe über alles
-  Rosettenhöhe
-  Grifflänge
-  Ausladung
-  Ausladung bis Mitte Bohrung
-  Einlasstiefe
-  Distanz Drückerloch – oberes Schraubenloch
-  Durchmesser (Bohrung, Dorn, Stange, Rohr, Seil oder Ansatz)
-  Stiftquerschnitt
-  Schraubenlochdistanz
-  Überschlag
-  Materialstärke
-  Gewinde, Schrauben, Bolzen
-  Mass A
-  Packungsgrösse/Staffelrabatt