


















Nagel geschmiedet

Eisen blank (geringe Korrosionsbeständigkeit)



Bezeichnung	Bestell-/Hersteller-Nr.	∅	St	CHF
Nagel geschmiedet	60.4279.18/030 mm	~10	St	0.30
Nagel geschmiedet	60.4279.18/035 mm	~11	St	0.40
Nagel geschmiedet	60.4279.18/040 mm	~11	St	0.50
Nagel geschmiedet	60.4279.18/050 mm	~12	St	0.65
Nagel geschmiedet	60.4279.18/060 mm	~12	St	0.85
Nagel geschmiedet	60.4279.18/070 mm	~13	St	1.15
Nagel geschmiedet	60.4279.18/080 mm	~15	St	1.35
Nagel geschmiedet	60.4279.18/090 mm	~14	St	1.60
Nagel geschmiedet	60.4279.18/100 mm	~15	St	2.00

Piktogramme für Massangaben

-  Breite über alles
-  Rosettenbreite
-  Höhe über alles
-  Rosettenhöhe
-  Grifflänge
-  Ausladung
-  Ausladung bis Mitte Bohrung
-  Einlasstiefe
-  Distanz Drückerloch – oberes Schraubenloch
-  Durchmesser (Bohrung, Dorn, Stange, Rohr, Seil oder Ansatz)
-  Stiftquerschnitt
-  Schraubenlochdistanz
-  Überschlag
-  Materialstärke
-  Gewinde, Schrauben, Bolzen
-  Mass A
-  Packungsgrösse/Staffelrabatt