

## Türgarnitur Serie Ochs


















Eisen naturblank (geringe Korrosionsbeständigkeit)




Bezeichnung	Bestell-/Hersteller-Nr.	H	I	H	ø	Ø	∩	CHF
<b>Türgarnitur</b>								Gt 398.00
Türdrücker	13.168.0	110	62	18	8			Pr 218.00
Drücker-Lochteil	13.168.2	110	62	18	8			St 109.00
Türschild ungelocht	13.105 UG	65	245	3	56	18		St 90.00
Türschild	13.105 BB78	65	245	3	56	18		St 90.00
Türschild	13.105 RZ78	65	245	3	56	18		St 90.00
Türschild	13.105 PZ78	65	245	3	56	18		St 90.00
Türschild	13.105 WC78-18	65	245	3	56	18		St 95.00



### Piktogramme für Massangaben

-  Breite über alles
-  Rosettenbreite
-  Höhe über alles
-  Rosettenhöhe
-  Grifflänge
-  Ausladung
-  Ausladung bis Mitte Bohrung
-  Einlasstiefe
-  Distanz Drückerloch – oberes Schraubenloch
-  Durchmesser (Bohrung, Dorn, Stange, Rohr, Seil oder Ansatz)
-  Stiftquerschnitt
-  Schraubenlochdistanz
-  Überschlag
-  Materialstärke
-  Gewinde, Schrauben, Bolzen
-  Mass A
-  Packungsgrösse/Staffelrabatt

### Standard-Lochungen



### Standard-Türstärken

- Zimmertüren: 40 mm
- Haustüren: 60 mm