

Sechskantschraube

Stahl vibropatiniert®



Bezeichnung	Bestell-/Hersteller-Nr.			CHF
Sechskantschraube	60.1988.14 6x30	100/10	St	1.50
Sechskantschraube	60.1988.14 6x40	100/10	St	1.70
Sechskantschraube	60.1988.14 6x50	100/10	St	2.00
Sechskantschraube	60.1988.14 6x60	100/10	St	2.30
Sechskantschraube	60.1988.14 8x30	100/10	St	2.60
Sechskantschraube	60.1988.14 8x40	100/10	St	3.10
Sechskantschraube	60.1988.14 8x50	100/10	St	3.60
Sechskantschraube	60.1988.14 8x60	100/10	St	4.10
Sechskantschraube	60.1988.14 8x70	100/10	St	4.60
Sechskantschraube	60.1988.14 8x80	100/10	St	5.10

Piktogramme für Massangaben

-  Breite über alles
-  Rosettenbreite
-  Höhe über alles
-  Rosettenhöhe
-  Grifflänge
-  Ausladung
-  Ausladung bis Mitte Bohrung
-  Einlasstiefe
-  Distanz Drückerloch – oberes Schraubenloch
-  Durchmesser (Bohrung, Dorn, Stange, Rohr, Seil oder Ansatz)
-  Stiftquerschnitt
-  Schraubenlochdistanz
-  Überschlag
-  Materialstärke
-  Gewinde, Schrauben, Bolzen
-  Mass A
-  Packungsgrösse/Staffelrabatt