

Türgarnitur Serie Spedia


















Eisen gerostet




Bezeichnung	Bestell-/Hersteller-Nr.	H	I	H	ø	∅	∩	CHF
Türgarnitur								Gt 410.00
Türdrücker	16.146.0	122	55	18	8			Pr 246.00
Drücker-Lochteil	16.146.2	122	55	18	8			St 123.00
Türschild ungelocht	16.147 UG	40	230	2	66	18		St 82.00
Türschild	16.147 BB78	40	230	2	66	18		St 82.00
Türschild	16.147 RZ78	40	230	2	66	18		St 82.00
Türschild	16.147 PZ78	40	230	2	66	18		St 82.00
Türschild	16.147 WC78-18	40	230	2	66	18		St 87.00



Piktogramme für Massangaben

-  Breite über alles
-  Rosettenbreite
-  Höhe über alles
-  Rosettenhöhe
-  Grifflänge
-  Ausladung
-  Ausladung bis Mitte Bohrung
-  Einlasstiefe
-  Distanz Drückerloch – oberes Schraubenloch
-  Durchmesser (Bohrung, Dorn, Stange, Rohr, Seil oder Ansatz)
-  Stiftquerschnitt
-  Schraubenlochdistanz
-  Überschlag
-  Materialstärke
-  Gewinde, Schrauben, Bolzen
-  Mass A
-  Packungsgrösse/Staffelrabatt

Standard-Lochungen



Standard-Türstärken

- Zimmertüren: 40 mm
- Haustüren: 60 mm