

Türgarnitur Serie Quadro


















Eisen thermopatiert®




Bezeichnung	Bestell-/Hersteller-Nr.	H	I	H	ø	Ø	∩	CHF
Türgarnitur								Gt 206.00
Türdrücker	12.137.0-14	125	57	14	8			Pr 140.00
Drücker-Lochteil	12.137.2-14	125	57	14	8			St 70.00
Türschild ungelocht	12.132/14 UG	38	237	3	74	14		St 33.00
Türschild	12.132/14 BB78	38	237	3	74	14		St 33.00
Türschild	12.132/14 RZ78	38	237	3	74	14		St 33.00
Türschild	12.132/14 PZ78	38	237	3	74	14		St 33.00
Türschild	12.132/14 WC78-18	38	237	3	74	14		St 38.00



Piktogramme für Massangaben

-  Breite über alles
-  Rosettenbreite
-  Höhe über alles
-  Rosettenhöhe
-  Grifflänge
-  Ausladung
-  Ausladung bis Mitte Bohrung
-  Einlasstiefe
-  Distanz Drückerloch – oberes Schraubenloch
-  Durchmesser (Bohrung, Dorn, Stange, Rohr, Seil oder Ansatz)
-  Stiftquerschnitt
-  Schraubenlochdistanz
-  Überschlag
-  Materialstärke
-  Gewinde, Schrauben, Bolzen
-  Mass A
-  Packungsgrösse/Staffelrabatt

Standard-Lochungen



Standard-Türstärken

- Zimmertüren: 40 mm
- Haustüren: 60 mm