

Türgarnitur Serie Next


















Eisen thermopatiert®




Bezeichnung	Bestell-/Hersteller-Nr.	H	I	H	ø	Ø	∩	CHF
Türgarnitur								Gt 199.00
Türdrücker	12.135.0	125	22	45	18	8		Pr 133.00
Drücker-Lochteil	12.135.2	125	22	45	18	8		St 66.50
Türschild ungelocht	12.132/18 UG	38	237	3	74	18		St 33.00
Türschild	12.132/18 BB78	38	237	3	74	18		St 33.00
Türschild	12.132/18 RZ78	38	237	3	74	18		St 33.00
Türschild	12.132/18 PZ78	38	237	3	74	18		St 33.00
Türschild	12.132/18 WC78-18	38	237	3	74	18		St 38.00



Piktogramme für Massangaben

-  Breite über alles
-  Rosettenbreite
-  Höhe über alles
-  Rosettenhöhe
-  Grifflänge
-  Ausladung
-  Ausladung bis Mitte Bohrung
-  Einlasstiefe
-  Distanz Drückerloch – oberes Schraubenloch
-  Durchmesser (Bohrung, Dorn, Stange, Rohr, Seil oder Ansatz)
-  Stiftquerschnitt
-  Schraubenlochdistanz
-  Überschlag
-  Materialstärke
-  Gewinde, Schrauben, Bolzen
-  Mass A
-  Packungsgröße/Staffelrabatt

Standard-Lochungen



Standard-Türstärken

- Zimmertüren: 40 mm
- Haustüren: 60 mm